

BS Varnish

Animal - Automotive - Common - Facility - Fireprevention - Home&Garden - Maritime - Sports

Product Description	Treatment	Specifications:
<p>Use and Benefits:</p> <p>Global Prefer® BS Varnish is a quickly drying paint for the fire protection coating Global Prefer® BS Timber. The Global Prefer® BS Varnish dries colorless and matt. The coating is meant to protect a surface treated with BS Timber from mechanical load and humidity and to improve the optical impression of the surface.</p> <ul style="list-style-type: none"> • Colorless protective coating for Global Prefer® BS Timber • Improves the decorative impression of the surface 	<p>Preparation:</p> <p>The surfaces must be free of dirt, separating particles and dry. Observe VOB (German Construction Contract Procedures), part C, DIN 18 363, paragraph 3. In each case either way, test the suitability on an unobtrusive spot.</p> <p>Application:</p> <p>Stir well before use. Global Prefer® BS Varnish can be processed as delivered. Global Prefer® BS Varnish is applied by means of coating, rolling or squirting. Dilution: If required, the fertility of the Global Prefer® BS Varnish can be increased by means of PVC or nitro thinners (observe the specification).</p> <p>Note:</p> <p>The thinner added to set the viscosity should not exceed 10%. If too much thinner is added, the quality may be reduced.</p> <p>Permanent effect:</p> <p>If processed appropriately, the coating can be effective for many years.</p> <p>Important Note:</p> <p>Drying: bone dry after 40 minutes (+10°C), 20 minutes (+20°C), 9 minutes (+35°C) touchproof after 60 minutes (+10°C), 30 minutes (+20°C), 15 minutes (+35°C) hardened after 4 hours (+10°C), 90 minutes (+20°C), 30 minutes (+35°C)</p> <p>Processing Temperature:</p> <p>Air: min.: + 8°C - max.: +35°C Object: min.: + 8°C - max.: +35°C Varnish: min.: + 10°C - max.: +35°C</p>	<p>Dilution:</p> <p>If required with 10% PVC or nitro thinner maximum</p> <p>Applied Quantity:</p> <p>as needed</p> <p>Processing Temperature:</p> <p>+8°C till +35°C Protect from direct sunlight.</p> <p>Storage and Service Life:</p> <p>Storable for at least 12 months as of the delivery date, if locked in original packaging unit. Seal opened packaging unit well. Protect from chill and direct sunlight.</p> <p>Storage Temperature:</p> <p>+8°C till +25°C</p> <p>Environmental Impact:</p> <p>Do not use it at temperatures below +8°C.</p> <p>Packaging Sizes:</p> <p>1000 ml spray flasks, 5 and 10 liter jerry cans; other sizes of trading unit on request.</p>

Artikelnummer	Produktbezeichnung	Gebindegröße	UVP (ohne MwSt.)	UVP (inkl. MwSt.)
1658	Brandschutz Klarlack	1000 ml	on request	on request
1659	Brandschutz Klarlack	5 Liter	on request	on request
1660	Brandschutz Klarlack	10 Liter	on request	on request